



## LAN printing for matrix and laser printers with optional IPDS transforms

**The EasyCom® III PrintServer from MPI Tech offers pristine LAN and IPDS connectivity for printers without a built-in network connection.**

### LAN connection for stand-alone printers

The EasyCom® III PrintServer is a pocket size hardware unit that connects primarily matrix printers but also laser printers without a built-in network port to the company LAN and turns them into network printers.

The EasyCom III PrintServer plugs directly into the parallel port, TCP/IP port or the USB port of the printer.

### Plug'n Print

EasyCom III is based on the MPI Tech Plug'n Print concept. When installing the PrintServer, just switch on the power and the installation manual is printed automatically. It can be installed either using a standard web browser, or the MPI Tech configuration tool, PrintGuide. Online access to manuals, technical support and upgrades is available world wide.

### LAN printing and IPDS host printing for matrix printers

EasyCom III IPDS Matrix version is developed to work efficiently in a mixed Host/LAN environment and supports TCP/IP sessions directly from the IBM systems as well as from the LAN. The EasyCom III IPDS Matrix converts the IPDS data to industry standard printer languages like IBM ProPrinter or Epson FX/LQ which are used by most line and matrix printers. The IPDS feature is an add-on function that is added via the product license key.

The EasyCom III IPDS Matrix PrintServer offers a number of unique printing features including Pre- and Poststrings as well as the power to substitute user defined print data using the Replacement strings technology.

To give optimal user value the EasyCom III IPDS Matrix print server supports most of the industry wide defined printing protocols. Among these IPP (Internet Printing Protocol) makes it easy to print across the Internet to any authorized printer on an IP network.

EasyCom III IPDS Matrix also provides capability to send status e-mails directly to the person responsible for the printer.

### High speed data transfer

Data transfer speeds exceeding 1 MByte/sec to the printer, programmable strings before and after jobs, automatic search and replace on incoming data, user defined queue naming in addition to 10 standard queue names, automatic download of data to printer at power up and status reporting to printer operator and system manager are just some of the exiting features of this product range.

With EasyCom III your printers are always connected.

### Key features

- ✓ LAN connection via the parallel port, serial port, USB 2.0 port or TCP/IP
- ✓ Optional IPDS, SCS and DCA support for matrix printers
- ✓ Optional SCS/DCA support using TN 3270/5250 with FSL support
- ✓ Plug'n Print
- ✓ Supports IPP (Internet Printing Protocol)
- ✓ Printer management using web, or PrintGuide™
- ✓ Status reporting using e-mail notification
- ✓ User defined Pre- and Poststrings
- ✓ User defined data substitution using Replacement strings
- ✓ Flash Upgradable



## Network Attachment

### Ethernet

100BASE-TX at 100 Mbps (IEEE 802.3u)

10BASE-T at 10 Mbps (IEEE 802.3)

### Printers:

Centronics parallel port (IEEE 1284, incl. ECP), Serial port Rs232, USB 2.0, TCP/IP

## System Support

### OS

Windows (10, 8, 7, Vista, Server 2012, 2008 R2, Server 2003), UNIX, Novell, Mac, HP-UX, AIX, IBM OS/400, OS/390, z/OS, MVS, VM, VSE

### Protocols

#### Printing:

TCP/IP, IPP, FTP

#### Booting:

DHCP, BOOTP, RARP

#### Configuration:

HTTP, DLC, TCP/IP, FTP, WINS, DNS

#### Status:

SNMP, DLC, TCP/IP, PING, SMTP

#### IBM Host system support

IBM zSeries, S/370, S/390 (MVS/VM/VSE),

IBM AS/400, iSeries, i5

## Minimum System Requirements (IPDS)

PSF/MVS Rel. 2.1 or higher

PSF/VM Rel. 2.1 or higher

PSF/VSE Rel. 2.2.0 or higher

GDDM 3.1

PSF/400 Rel. 3.1 or higher

InfoPrint Manager for Windows Ver 2R2

InfoPrint Manager for AIX Ver 4R2

## Emulation (optional)

Emulations are activated through the license key

### IPDS

IBM 4247 (using IBM ProPrinter or Epson language)

### SCS

IBM 3268/4214, 3287

### DCA

IBM 3812/5219,5224, 5225, 5256, 4234

## Printers Supported

One printer with:

- PCL 5/5c,
- PostScript L2/L3,
- IBM ProPrinter
- or Epson FX/LQ

Ask for other printer types.

## Printer Connection

- Parallel port,
- USB output port
- Network port via TCP/IP

## Features

Multi session/multi protocol support, dynamic PC printer share, Pre, post and replacement string facility, Firmware upgrade via PrintGuide™, Password protected setup.

### Substitution Strings:

Search/Replace. If, for example, the company changes telephone number, you can specify via the web server that the new one should be printed in all documents.

### Strings at Power on, Before and/or After Print Job:

The Print Servers can send pre-defined settings to the printer, such as the company logo, a particular font or the Euro currency symbol.

### E-mail notification:

The Print Servers will notify you when the printer has run out of paper, when there is a paper jam, or in a variety of other situations.

### SCS/DCA features (optional)

MPI Tech FSL facility, Advanced font handling, Multiple page formats, Automatic page orientation, Advanced paper size handling, Internal barcode generation, MPI Tech PSS/EPM AFP software support.

### IPDS features (optional)

Full IPDS support, 2D barcode, True-page counters, page offset functions. IBM 4247 resident font set.

## Set-up

- MPI Tech PrintGuide™ (Windows)
- Web browser (HTML),
- Auto-configuration
- DHCP server
- TELNET

## Management

Web browser (HTTP/HTML), PrintGuide™ (DLC/TCP/IP), e-mail notification using SMTP, SNMP MIB II, File based using FTP.

## Regulatory information

### Safety

73/23/EEC-Low voltage directive:

- EN60950-1:2001
- UL60950-1 (CSA C22.2 No:60950-1-3)

### EMC

89/336/EEC - EMC directive:

- EN 55022: 1998 + A2:2003, Class B
  - EN 55024: 1998 + A1:2001 + A2:2003
- FCC 47 CFT Part 15, Class A

AS/NZS 3548 Class B

### Environmental

- 2011/65/EC - RoHS directive
- 2002/96/EC - WEEE directive
- 2006/122/EC - PFOS directive

### Warranty

1 year manufacturing fault warranty

### Size / Weight

97 x 60 x 20mm / 3.8 x 2.4 x 0.8"

Weight: 68g / 2.4oz / 0.1lb

### Power Requirements

5V 500mA (Power supply included)

### Versions

#### EasyCom III

Single Port fast Ethernet connection

#### EasyCom III SCS/DCA

Matrix SCS/DCA support with FSL

#### EasyCom III IPDS + SCS/DCA

Matrix IPDS support to Matrix printers

## Our offices

### France

40, rue du Général Malleret Joinville  
BP 88 - 94402 Vitry sur Seine Cedex  
Phone: +33 (0)1 4573 0940  
Fax: +33 (0)1 4680 7071  
E-mail: sales.fr@mpitech.com

### Denmark

Vadstrupvej 35  
DK-2880 Bagsvaerd  
Phone: +45 4436 6000  
E-mail: sales.dk@mpitech.com

### United Kingdom

Anchor House, 50 High Street  
Bagshot GU19 5AW  
Phone: +44 (0)844 800 9803  
Fax: +44 (0)1276 452 379  
E-mail: sales.uk@mpitech.com

### Germany

Bavariastrasse 7a  
D-80336 Muenchen  
Phone: +49 (0)89 35 4762 20  
Fax: +49 (0)89 35 4762 11  
E-mail: sales.de@mpitech.com

### North America - West Coast

4952 Warner Avenue, Suite 301  
Huntington Beach, CA 92649-5506  
Phone: +1 (714) 840 8077  
Fax: +1 (714) 840 2176  
E-mail: sales.us@mpitech.com

### North America - East Coast

2001 Jefferson Davis Highway, Suite 306  
Arlington, VA 22202  
Phone: +1 (703) 418 0680  
Fax: +1 (703) 418 0684  
E-mail: sales.us@mpitech.com



D16112-009 October 2016

Company and product names mentioned in this text are trademarks or registered trademarks of their respective owners. MPI Tech A/S cannot be held responsible for any technical or typographical errors and reserves the right to make changes to products and documentation without prior notification.